



1. CONCRETE FOUNDATION TO BE INSTALLED ON COMPACTED VIRGIN SOIL NEXT TO PIPE TRENCH.
2. TOP OF THE FOUNDATION MUST BE 100mm BELOW NATURAL GROUND LEVEL.
3. TOP OF SURROUND TO BE AT NATURAL GROUND LEVEL.



MATERIALS LIST			
ITEM	QTY.	DESCRIPTION	MATERIAL / REFERENCE
1	1	TYPICAL CONCRETE TEST POST BUNKER	PRE-CAST CONCRETE
2	1	LOCKABLE DOOR CAST-IN	STEEL (GALVANIZED)
3	2	DOOR HANDLES	3mm GRADE MS
4	AS REQD	MASS CONCRETE FOUNDATION 1200x1000x100	CAST IN-SITU
5	AS REQD	PVC TUBE FILLED WITH SAND	60mmØ PVC CONDUIT
6	AS REQD	REINFORCING MESH	200 x 200 x 6mm STEEL WELD MESH
7	AS REQD	CONCRETE SURROUND 100 THK.	CAST IN-SITU

No	Date	Details	Chd	App'd
Revisions				



Client



Approved By

Drawn By

Designed By	
-------------	--

Reviewed By

Project

LINBRO PARK TOWER  
 (AND ASSOCIATED WORKS)  
 CP DESIGN

#### Description

BUNKER TEST  
POST ENCLOSURE

Scale

AS SHOWN

Date \_\_\_\_\_

2023/02/1

Drawing No.

PES-PEP0221-CP-002

R

/ 0