



MEMBER	No OF	BARS PER MEMB	DIA.	LENGTH	TOTAL NUM- BER	MARK	S C	B E N D I N G				
								A	B	C	D	E/r
	1	2	Y20	7900	2	10ab	55	550	1550	3870	1550	(550)
		2	Y20	7450	2	10ac	55	550	1550	3420	1550	(550)
		2	Y20	6900	2	10ad	55	550	1550	2900	1550	(550)
		2	Y20	6250	2	10ae	55	550	1550	2220	1550	(550)
		2	Y20	5200	2	10af	55	550	1550	1170	1550	(550)
		2	Y16	9200	2	11a	38	800	7650	(800)		
		2	Y16	9150	2	11b	38	800	7630	(800)		
		2	Y16	9100	2	11c	38	800	7580	(800)		
		2	Y16	9050	2	11d	38	800	7520	(800)		
		2	Y16	8950	2	11e	38	800	7430	(800)		
		2	Y16	8750	2	11f	38	800	7230	(800)		
		2	Y16	8700	2	11g	38	800	7190	(800)		
		2	Y16	8550	2	11h	38	800	7040	(800)		
		2	Y16	8400	2	11i	38	800	6850	(800)		
		2	Y16	8150	2	11j	38	800	6640	(800)		
		2	Y16	7900	2	11k	38	800	6390	(800)		
		2	Y16	7650	2	11l	38	800	6110	(800)		
		2	Y16	7300	2	11m	38	800	5790	(800)		
		2	Y16	6950	2	11n	38	800	5420	(800)		
		2	Y16	6500	2	11o	38	800	4990	(800)		
		2	Y16	6000	2	11p	38	800	4480	(800)		
		2	Y16	5400	2	11q	38	800	3870	(800)		
		2	Y16	4600	2	11r	38	800	3080	(800)		
		2	Y16	3450	2	11s	38	800	1940	(800)		
		2	Y20	11550	2	12a	55	550	1500	7650	1500	(550)
		2	Y20	11550	2	12b	55	550	1500	7640	1500	(550)
		2	Y20	11550	2	12c	55	550	1500	7630	1500	(550)
		2	Y20	11500	2	12d	55	550	1500	7600	1500	(550)
		2	Y20	11500	2	12e	55	550	1500	7570	1500	(550)
		2	Y20	11450	2	12f	55	550	1500	7530	1500	(550)
		2	Y20	11400	2	12g	55	550	1500	7490	1500	(550)
		2	Y20	11350	2	12h	55	550	1500	7430	1500	(550)
		2	Y20	11300	2	12i	55	550	1500	7370	1500	(550)
		2	Y20	11200	2	12j	55	550	1500	7300	1500	(550)
		2	Y20	11150	2	12k	55	550	1500	7220	1500	(550)
		2	Y20	11050	2	12l	55	550	1500	7130	1500	(550)
		2	Y20	10950	2	12m	55	550	1500	7040	1500	(550)
		2	Y20	10850	2	12n	55	550	1500	6930	1500	(550)
		2	Y20	10700	2	12o	55	550	1500	6810	1500	(550)
		2	Y20	10600	2	12p	55	550	1500	6680	1500	(550)
		2	Y20	10450	2	12q	55	550	1500	6540	1500	(550)
		2	Y20	10300	2	12r	55	550	1500	6390	1500	(550)
		2	Y20	10150	2	12s	55	550	1500	6230	1500	(550)
		2	Y20	9950	2	12t	55	550	1500	6050	1500	(550)
		2	Y20	9750	2	12u	55	550	1500	5860	1500	(550)
		2	Y20	9550	2	12v	55	550	1500	5650	1500	(550)
		2	Y20	9350	2	12w	55	550	1500	5420	1500	(550)
		2	Y20	9100	2	12x	55	550	1500	5170	1500	(550)
		2	Y20	8800	2	12y	55	550	1500	4890	1500	(550)
		2	Y20	8500	2	12z	55	550	1500	4590	1500	(550)
		2	Y20	8150	2	12aa	55	550	1500	4250	1500	(550)
	8	10	12	16	20	25	32	40	TOT	Date	2023/09/14	
R										Det. by	AM 	
Y				454	1566				2019	Ref Dwg	C01486-SR01	
TOT				454	1566				2019	Job No	J147	
				JW14406 - LINBRO PARK TOWER (3.0ML WATER TOWER): PILE CAPS AND BEAMS REINFORCEMENT BENDING SCHEDULE						Revision		0
										Schedule No		C01486-SR01-BS02