	ı				1			
Turbine Hall 65 Ntemi Piliso						PA	GE NO.	
Newtown								
P O Box 61542						CLOSING D	ATE AND TIME	
Marshalltown 2107 Tel: (011) 688-1400	7					26-May-25	16:00	
Fax: (011) 688-1556			Johannesburg Water			Date	of Issue lay 2025	
	INITIATING DEPARTMENT Electrical Support	INITIATOR Bongi Buthelezi	Johannesburg Water	QUOTATION DATE			lay 2025 LIDITY	
	QUOTATION REFERENCE	COLLECTIVE NO.		60 DAYS			DAYS	
RFQJW0092SM202 tags	25 -supply, deliver, and install a key cabinet with a	capacity of 300 keys, including numbered hooks and 300 key						
tugo	QUOTATION REQUE	STED FROM						
			QUOTATIONS WILL BE EVALUATED ON THE 80/20 POINT S	SCORING SYSTEM. 80	POINTS WILL BE AL	LOCATED TO PRI	CE AND THE REMA	INING 20 POINTS
			WILL BE ALLOCATED FOR SPECIFIC GOALS AS FER FFF	A 2022				
			ALL SUPPLIERS RESPONDING TO QUOTATIONS SHOULD JW Contact Person: Simphiwe Mdlalose - Email Address:			DATABASE (CSD)	
			Telephone Number : 011 688 1825					
			Telephone Number : 011 666 1625					
ITEM NO.	E	DESCRIPTION	DESCRIPTION OF ITEM OFFERED	UOM	QTY REQUIRED	PRICE QUOTED EXCL. OF V.A.T.	DISCOUNT	PRICE QUOTED INCL. OF V.A.T.
					1			
	supply, deliver, and install a key cabinet with a capacity of 300 keys, including numbered hooks and 300 key tags				<u> </u>			
	Specifications							1
	Electronic locking key cabinet for wall mounti							
	The cabinet can be easly wall mounted using		-					
	Well constructed with high quality steel and v	very sturdy, hard wearing						
	Galvanized, shining zinc or Light gray - plated	alvanized, shining zinc or Light gray - plated hook - strips offer rust prevention also at the cutting edges.						
	Secured by a chrome plated cylinder lock and supplied with an Electronic Lock							
	Body and door made of quality thin-sheet metal. Sturdy finishing.							
	Flat keyboard with LED lights							
	Emergency Opening:Mechanical emergency opening with key					L		
	Chrome-plated cylinder lock with 2 keys.							
	Battery saving by mechanical locking and unlocking, using the rotating handle							
	Battery operated, requires 4 x AA 1,5 V (To be supplied by the tenderer)							
	Outer dimension (mm) Height x Width x Depth (550 x 380 x 205)							
	Weight KG:Approximetely 13.8							
	Handle:Twist grip							
	Tenderers are required to submit datasheets and photos of the quoted product. Failure to do so will result in disqualification							
	Contact Person: Kippie							
	Contact Number : 083 503 4257							
	QOUTATION TO BE VALID FOR 60 DAYS AND REFLECTING ON THE QOUTE							
		1						
	SPECIFIC GOALS	POINTS						
	EME's OR QSE's- Businesses owned by people who are black- 51% or more	20						
	QUOTATION REF AS ABOVE: RFQJW& COMPANY NAME NB: All suppliers responding to RFQs should use their own company letter head not JW RFQ Template AND MAKE SURE THEIR EMAIL							
	ADDRESS IS VISIBLE ON THEIR QUOTATION.							
	NB: A copy of valid lease agreement or municipal account(not older than 3 months)should be submitted with a quote							
	NB: MBD forms attached should be completed and submitted with the quote NB: All Quotes should be on PDF (MS WORD, MS EXCEL, PICTURES ARE NOT ALLOWED)							
	NB: All Quotes should be on PDF (MS WORD, MS EXCEL, PICTURES ARE NOT ALLOWED) NB: Copy of valid BBBEE CERTIFCATE or SWORN AFFIDAVIT to be submitted with the quote							
	Quotation should be valid for 60 days							
	Send All quotations to: jw.directsquotations@jwater.co.za							
	outer in quotations to fir an outequotation of in the toolse							
		=						
	OFFICIAL STAMP	AUTHORISED BY:	1. QUOTATIONS RECEIVED AFTER CLOSE OF BUSINESS (ON THE CLOSING DAT	E WILL NOT BE ACC	EPTED.		
		SIGNATURE:	3. PRICES QUOTED MUST BE AS PER THE UNIT INDICATE	HOUT BRAND NAMES WHERE REQUIRED WILL NOT BE ACCEPTED MUST BE AS PER THE UNIT NIDICATED AND BE EXCLUDED OF VAT HOUT THE SUPPLIER'S AUTHORISED SIGNATURE WILL NOT BE ACCEPTED. (ONLY IF QUOTED ON THE JW RFQ A QUOTATION WILL BE SUBJECT TO JOHANNESBURG WATER'S SUPPLY CHAIN POLICY				
		DATE:	5. ACCEPTANCE OF A QUOTATION WILL BE SUBJECT TO					
D11 L			6. TOTAL QUOTATION VALUE TO INCLUDE V.A.T WHERE APPLICABLE					